

Tanques precargados con diafragma, tipo vertical



Serie water pro

Serie Water Pro (presión máx. 125 lb/pulg²)


Modelo	Capacidad		Precargado (lb/pulg ²)	Descarga	Dimensiones		Entrega (galones) (PSI)			Peso* (kg)	Precio de lista
	(gal)	(litros)			Ø	Altura	30/50	40/60	50/70		
WP20	20	76	28	1"	15"	32"	6.8	5.9	4.7	15.9	US\$
WP26	26	98	28	1"	15"	38"	8.8	7.6	6.1	16.4	US\$
WP44	44	166	38	1¼"	22"	36"	15	12.9	10.4	31.4	US\$
WP62	62	235	38	1¼"	22"	47"	21.1	18.2	14.6	41.8	US\$
WP86	86	326	38	1¼"	26"	47"	29.2	25.3	20.3	55.9	US\$
WP119	119	450	38	1¼"	26"	62"	40.5	35	28.1	75.5	US\$

* Aproximado.

- Cuentan con 5 años de garantía.



Serie Well-X-Trol Tuf-Kote



Serie Well-X-Trol Tuf-Kote™ (modelos en línea)

Modelo	Capacidad		Factor de máxima aceptación	Conexiones (NPTF)	Dimensiones		Entrega (galones) (PSI)			Peso* (kg)	Precio de lista
	(gal)	(litros)			A	B	30/50	40/60	50/70		
WX101	2	8	0.45	3/4"	13"	8"	0.6	0.6	0.5	2	US\$
WX102	4.4	17	0.55	3/4"	15"	11"	1.4	1.2	1	4	US\$
WX103	7.6	29	0.43	3/4"	22"	11"	2.4	2	1.8	7	US\$
WX104	10.3	39	1	1"	18"	15"	3.2	2.8	2.4	9	US\$

* Aproximado.

- Cuentan con 7 años de garantía.