


Tanques precargados con diafragma, tipo vertical



Serie Well-X-Trol ASME



Serie Flotec

Serie Well-X-Trol ASME - 175 PSI

Modelo	Capacidad		Factor de máxima aceptación	Dimensiones					Descarga	Peso* (kg)	Precio de lista
	(gal)	(litros)		A	B	C	D	E			
WX401C-175	18	68	0.65	31"	16"	5"	1½"	12¾"	1"	50	US\$
WX402C-175	25	95	0.45	40"	16"	5"	1½"	12¾"	1"	57	US\$
WX403C-175	34	129	0.33	49"	16"	5"	1½"	12¾"	1"	66	US\$
WX404C-175	68	258	0.5	48"	24"	6"	1½"	16"	1¼"	142	US\$
WX405C-175	90	341	0.39	59"	24"	6"	1½"	16"	1¼"	174	US\$
WX406C-175	110	417	0.31	70"	24"	6"	1½"	16"	1¼"	182	US\$
WX407C-175	132	500	0.35	57"	30"	10"	1¾"	24"	1¼"	231	US\$

Serie Well-X-Trol ASME - 250 PSI

Modelo	Capacidad		Factor de máxima aceptación	Dimensiones					Descarga	Peso* (kg)	Precio de lista
	(gal)	(litros)		A	B	C	D	E			
WX401C-250	18	68	0.65	31"	16"	5"	1½"	12¾"	1"	57	US\$
WX402C-250	25	95	0.45	40"	16"	5"	1½"	12¾"	1"	65	US\$
WX403C-250	34	129	0.33	49"	16"	5"	1½"	12¾"	1"	83	US\$
WX404C-250	68	258	0.5	48"	24"	6"	1½"	16"	1¼"	186	US\$
WX405C-250	90	341	0.39	59"	24"	6"	1½"	16"	1¼"	196	US\$
WX406C-250	110	417	0.31	70"	24"	6"	1½"	16"	1¼"	215	US\$
WX407C-250	132	500	0.35	57"	30"	10"	1¾"	24"	1¼"	259	US\$

* Aproximado.

- Todos los modelos Well-X-Trol® ASME cuentan con 1 año de garantía.

Serie Flotec (presión máx. 125 lb/pulg²)

Modelo	Equivalencia (galones)	Capacidad (galones)	Conexiones (NPTF)	Entrega (galones) (PSI)						Peso* (kg)	Precio de lista
				Precargado			Estándar				
				20/40	30/50	40/60	20/40	30/50	40/60		
FP7125	120	50	1¼"	18.3	15.5	13.4	18.6	12.2	8.8	37.4	US\$
FP7130	220	85	1¼"	30	26	22	34.1	22.4	16.1	53.4	US\$

* Aproximado.

- Cuentan con 1 año de garantía.